

# 4K HD Intelligent ColorHunter Fixed Eyeball Network Camera

IPC3638SE-ADF28(40)K-WL-I0



## Features

- High quality image with 8MP, 1/1.8"CMOS sensor
- 8MP (3840\*2160)@ 30(Intelligent off)/25fps; 5.3MP (3072\*1728)@ 30/25fps; 3.6MP (2560\*1440) @30/25fps; 2MP (1920\*1080) @30/25fps; 720P (1280\*720), Max 30/25fps
- Ultra 265, H.265, H.264, MJPEG
- Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
- Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human and, motor vehicle and non-motor vehicle
- Intelligent People Flow Counting and Crowd Density Monitoring
- Colorhunter technology ensures 24-hour full-color images
- F1.0 Super aperture
- 120dB true WDR technology enables clear image in strong light scene
- Support 9:16 corridor Mode
- Alarm:1 in/1 out, Audio: 1 in/1 out
- Supports 512 G micro SD card
- IK10 vandal resistant and IP67 protection

## Specifications

|                                    |                                                   |                |                        |
|------------------------------------|---------------------------------------------------|----------------|------------------------|
| Model                              | IPC3638SE-ADF28K-WL-I0                            |                | IPC3638SE-ADF40K-WL-I0 |
| Camera                             |                                                   |                |                        |
| Max Resolution                     | 8 MP                                              |                |                        |
| Sensor                             | 1/1.8" CMOS                                       |                |                        |
| Min. Illumination                  | Colour: 0.0005 lux (F1.0, AGC ON)                 |                |                        |
| Shutter                            | Auto/Manual, 1 ~ 1/100000s                        |                |                        |
| Adjustment Angle                   | Pan: 0° ~ 360°, Tilt: 0° ~ 72°, Rotate: 0° ~ 360° |                |                        |
| S/N                                | >56 dB                                            |                |                        |
| WDR                                | 120 dB                                            |                |                        |
| Lens                               |                                                   |                |                        |
| Focal Length                       | 2.8 mm                                            | 4.0 mm         |                        |
| Iris Type                          | Fixed                                             |                |                        |
| Iris                               | F1.0                                              |                |                        |
| Field of View (H)                  | 113.5°                                            | 94.3°          |                        |
| Field of View (V)                  | 68.3°                                             | 49.7°          |                        |
| Field of View (D)                  | 133.0°                                            | 115.9°         |                        |
| DORI                               |                                                   |                |                        |
| DORI Distance (Lens)               | 2.8mm                                             | 4.0mm          |                        |
| DORI Distance (Detect)             | 63.0m(206.7ft)                                    | 90.0m(295.3ft) |                        |
| DORI Distance (Observe)            | 25.2m(82.7ft)                                     | 36.0m(118.1ft) |                        |
| DORI Distance (Recognize)          | 12.6m(41.3ft)                                     | 18.0m(59.1ft)  |                        |
| DORI Distance (Identify)           | 6.3m(20.7ft)                                      | 9.0m(29.5ft)   |                        |
| Illuminator                        |                                                   |                |                        |
| Supplemental Light                 | Warm light                                        |                |                        |
| Illumination Distance (Warm Light) | 30 m (98.4 ft)                                    |                |                        |
| Light On/Off Control               | Auto/Manual                                       |                |                        |
| Video                              |                                                   |                |                        |
| Video Compression                  | Ultra 265, H.265, H.264, MJPEG                    |                |                        |


|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frame Rate                 | Main Stream: 8MP (3840*2160), Max 30fps; 5.3MP (3072*1728), Max 30fps; 3.6MP (2560*1440), Max 30fps; 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps;<br>Sub Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;<br>Third Stream: D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; |
| H.264 Code Profile         | Baseline profile, Main profile, High profile                                                                                                                                                                                                                                                                                                                                                                                                             |
| Video Bit Rate             | 128 Kbps to 16 Mbps                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| U-code                     | Support                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| OSD                        | Up to 8 OSDs                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Privacy Mask               | Up to 4 areas                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| ROI                        | Support                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Video Stream               | Triple Streams                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Image</b>               |                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Smart Illumination         | Support                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| White Balance              | Auto, Outdoor, Fine Tune, Sodium Lamp, Locked, Auto2                                                                                                                                                                                                                                                                                                                                                                                                     |
| Digital Noise Reduction    | 2D/3D DNR                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Flip                       | Normal, Flip Vertical, Flip Horizontal, 180°, 90°Clockwise, 90°Anti-clockwise                                                                                                                                                                                                                                                                                                                                                                            |
| Dewarping                  | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| HLC                        | Support                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| BLC                        | Support                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Defog                      | Digital Defog                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Intelligent</b>         |                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Smart Intrusion Prevention | Cross line detection, intrusion detection, enter area detection, leave area detection (support false alarm filtering and the classification of human, non-motor vehicle and vehicle)                                                                                                                                                                                                                                                                     |
| Statistical Analysis       | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| People Counting            | Support People Flow Counting and Crowd Density Monitoring                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Events</b>              |                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Basic Detection            | Motion Detection, Ultra Motion Detection, Tampering Alarm, Audio Detection                                                                                                                                                                                                                                                                                                                                                                               |
| General Function           | Watermark, IP Address Filtering, Access Policy, ARP Protection, RTSP Authentication, User Authentication, HTTP Authentication                                                                                                                                                                                                                                                                                                                            |
| <b>Audio</b>               |                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Audio Compression          | G.711U, G.711A                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Audio Bitrate              | 64 Kbps                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Two-way Audio              | Support                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Suppression                | Support                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Sampling Rate              | 8 kHz                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Storage</b>             |                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Edge Storage               | Micro SD, up to 512 GB                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Network Storage            | ANR, NAS (NFS)                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Network</b>             |                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

|                        |                                                                                                                                                                                                            |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protocols              | IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, SSL/TLS, SSH                                                   |
| Compatible Integration | ONVIF (Profile S, Profile G, Profile T, Profile M), API, SDK                                                                                                                                               |
| User/Host              | Up to 32 users, 2 user levels: administrator and common user                                                                                                                                               |
| Security               | Password Protection, Strong Password, HTTPS Encryption, Export Operation Logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, TLS 1.2, WSSE and Digest Authentication for ONVIF |
| Client                 | UNV-Link, UNV-Link Pro, EZStation                                                                                                                                                                          |
| Web Browser            | Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+                                                                           |
| <b>Interface</b>       |                                                                                                                                                                                                            |
| Audio I/O              | 1 Input: impedance 35 kΩ, amplitude 2 V [p-p], 1 Output: impedance 600 Ω, amplitude 2 V [p-p]                                                                                                              |
| Alarm I/O              | 1/1                                                                                                                                                                                                        |
| Serial Port            | N/A                                                                                                                                                                                                        |
| Built-in Mic           | Support                                                                                                                                                                                                    |
| Built-in Speaker       | N/A                                                                                                                                                                                                        |
| WIFI                   | N/A                                                                                                                                                                                                        |
| Network                | 1 × RJ45 10 M/100 M Base-TX Ethernet                                                                                                                                                                       |
| Video Output           | N/A                                                                                                                                                                                                        |
| <b>Certification</b>   |                                                                                                                                                                                                            |
| EMC                    | CE-EMC (EN 55032: 2015+A1:2020, EN 61000-3-3: 2013+A1: 2019, EN IEC 61000-3-2: 2019+A1: 2021, EN 55035: 2017+A11:2020)<br>FCC (FCC CFR 47 part15 B, ANSI C63.4-2014)                                       |
| Safety                 | CE LVD (EN 62368-1:2014+A11:2017)<br>CB (IEC 62368-1:2014)<br>UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01)                                                                                             |
| Environment            | CE-RoHS (2011/65/EU; (EU)2015/863); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)                                                                                                                |
| Protection             | IP67 (IEC 60529:1989+AMD1:1999+AMD2:2013)<br>IK10 (IEC 62262:2002)                                                                                                                                         |
| <b>General</b>         |                                                                                                                                                                                                            |
| Power                  | DC 12V±25%, PoE (IEEE 802.3af)                                                                                                                                                                             |
| Power Consumption      | Max 11.0W                                                                                                                                                                                                  |
| Power Interface        | Ø5.5 mm coaxial power plug                                                                                                                                                                                 |
| Dimensions             | Ø129 x 110mm (Ø5.1" x 4.3") (Ø x H)                                                                                                                                                                        |
| Weight                 | 0.64kg (1.41lb)                                                                                                                                                                                            |
| Material               | Metal                                                                                                                                                                                                      |
| Working Environment    | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                                                                                                    |
| Storage Environment    | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                                                                                                    |
| Surge Protection       | 4 KV                                                                                                                                                                                                       |
| Reset Button           | Support                                                                                                                                                                                                    |

Web Client  
Language

20 Languages: Traditional Chinese, English, Simplified Chinese, Polish, German, Russian, French, Korean, Dutch, Czech, Portuguese (Europe), Portuguese (Brazil), Japanese, Thai, Turkish, Spanish (Latin America), Spanish (Europe), Hungarian, Italian, Vietnamese

## Dimensions



## Accessories

TR-JB03-H-IN

Junction Box for Metal Turret Camera(Support wiring from behind)



TR-JB07/WM03-F-IN

Wall Mounting Assembling Bracket with Back Hole for 3 Inch Hemisphere



TR-WM03-B-IN

Wall Mounting Assembling Bracket for 3 Inch Hemisphere



TR-A01-IN

NPT 3/4" Waterproof Cable Gland



TR-UP06-IN

Universal Pole Mounting Bracket



TR-UC08-C

Bullet&Dome Corner Mounting Bracket



TR-SE24-IN

Dome Pendant Mounting Pole 200mm



TR-SE24-A-IN

Dome Pendant Mounting Pole 500mm



TR-CM24-IN

Dome Pendant Mounting Bracket(Indoor)



### Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.