


FP0150/250-3C42D8E8M

Mercury Unified Power Systems 400W Dual Voltage, 120 VAC 12 Relay Lock Outputs 16 Auxiliary Outputs



ELECTRICAL RATINGS

Parameter	Rating
Input Voltage	120 VAC, 50/60Hz
Input Power (max)	452W
Output Power	400W
Relay Lock Outputs	12 @ 3A Fused
Auxiliary Outputs	16 @ 3A Fused
Maximum Charge Current	FPO150: 2A, 80AH maximum
	FPO250: 2A, 80AH maximum
Low Power Disconnect	at 70% of battery voltage
Systems BTU/Hr	175 BTU/Hr
Operating Temperature	32 to 122F (0 to +50C)
Efficiency	87% 120VAC 60Hz In, Full Load
Agency Approvals	UL294, UL603, UL1076, ULC
	S318, ULC S319, CSA C22.2
	#205, FCC Part 15, Subpart B,
	CSFM IEC 62368-1:2014, EN
	55032:2015, EN6100-3-2:2014,
	EN6100-3-3:2013,
	EN55024:2010+A1:2015, BIS
	IS13252(Part 1):2010, REACH

209, ROHS 3

OVERVIEW

Mercury Unified Power Systems combine FlexPower power modules alongside access control hardware in one compact and secure UL listed solution. Unified Power features include:

- Built in Fire Alarm disconnect unlocks doors on a fire alarm
- Low battery cutoff protects batteries from deep discharge
- Dedicated fast charger prolongs battery life
- Enhanced surge immunity for input/output protection
- Locksafe optimized voltages provide long-term lock protection
- OutSmart Visual LED notification (12V/Green, 24V/Blue)
- Network ready with optional LifeSafety Power NetLink® module

 Monitor power supply and battery in NetLink dashboard
 Remote test batteries
- · Lifetime Warranty LifeSafety Power's quality commitment

SYSTEM DETAILS

- 1 x FP0150, 1 x FP0250 400W Total Output, 120 VAC Input, AC Fault and System Fault form C contacts may be triggered by low/no battery, short to earth ground, power supply failure, or blown fuse
- **3 x C4 (12 Relay Lock Outputs)** 3A fused outputs, programmable for failsafe/failsecure, FAI, NC/NO input, voltage or dry output per zone. Dual buss voltage selection by zone, OutSmart dual color LEDs
- 2 x D8 (16 Auxiliary Outputs) 3A fused Outputs, dual buss voltage selection by zone, OutSmart dual color LEDs
- E8M Enclosure Size: 36.0H x 30.0W x 6.5D in (91.44 x 76.20 x 16.51 cm)
 Enclosure E8 E8 enclosure size 36H x 30W x 6.5D
 - Backplate E8M Backplate mounting for LP1502, LP4502, LP2500, MR52, MR16IN/OUT
- System Weight 63.85 lbs (28.96kg)

ORDERING

FP0150/250-3C42D8E8M

120 VAC, 400W, 12 Lock, 16 Aux

AGENCY LISTINGS

US | Canada | Mexico | Europe | UK | India | Australia | New Zealand | RoHS



LifeSafety Power

10027 S. 51st Street, Suite 102 Phoenix, AZ 85044 USA (888) 577-2898 info1@lifesafetypower.com

Disclaimer:

This datasheet was generated programatically by LifeSafety Power's Online Product Generator on 03/24/2025. Because of this, it may be possible that the model depicted is not possible for LifeSafety Power to build. It is the responsibility of the viewer of this datasheet to confirm that the model depicted is within the limitations of the product line. Contact LifeSafety Power for confirmation of fitment or compatibility. Specifications subject to change without notice.