

## **ELECTRICAL RATINGS**

Parameter	Rating
Input Voltage	Input, 50/60Hz
Input Power (max)	0W
Output Power	0W
Maximum Charge Current	
Low Power Disconnect	at 70% of battery voltage
Systems BTU/Hr	0 BTU/Hr
Operating Temperature	32 to 122F (0 to +50C)
Efficiency	0% 120VAC 60Hz In, Full Load
Agency Approvals	UL294, UL1076, ULC S318, ULC
	S319, CSA C22.2 #107.1, FCC
	Part 15, Subpart B, CSFM IEC
	62368-1:2014, EN 55032:2015,
	EN6100-3-2:2014, EN6100-3-
	3:2013, EN55024:2010+A1:2015,
	BIS IS13252(Part 1):2010, NOM-
	001-SCFI-1933, REACH 209,
	ROHS 3, RCM AS/NZS 4417.1,
	SAA AS/NZS 62368.1:2018

#### OVERVIEW

Power Systems combine FlexPower power modules alongside access control hardware in one compact and secure UL listed solution. Unified Power features include:

- Built in Fire Alarm disconnect unlocks doors on a fire alarm
- · Low battery cutoff protects batteries from deep discharge
- · Dedicated fast charger prolongs battery life
- Enhanced surge immunity for input/output protection
- Locksafe optimized voltages provide long-term lock protection
- OutSmart Visual LED notification (12V/Green, 24V/Blue)
- Network ready with optional LifeSafety Power NetLink® module
  - Monitor power supply and battery in NetLink dashboard
  - Remote test batteries
- Lifetime Warranty LifeSafety Power's quality commitment

## SYSTEM DETAILS

• System Weight 0 lbs (0.00kg)

#### ORDERING

NPM130DR-Boxed

VAC, 0W

# AGENCY LISTINGS

US | Canada | Mexico | Europe | UK | India | Australia | New Zealand | RoHS



















# **LifeSafety Power**

10027 S. 51st Street, Suite 102 Phoenix, AZ 85044 USA (888) 577-2898 info1@lifesafetypower.com

# Disclaimer:

 $This\ datasheet\ was\ generated\ program at ically\ by\ LifeSafety\ Power's\ Online\ Product\ Generator\ on$ 03/31/2025. Because of this, it may be possible that the model depicted is not possible for LifeSafety Power to build. It is the responsibility of the viewer of this datasheet to confirm that the model depicted is within the limitations of the product line. Contact LifeSafety Power for confirmation of fitment or  $compatibility. \ Specifications \ subject \ to \ change \ without \ notice.$