

### Overview

MCLASS multi-purpose enclosures offer maximum flexibility, functionality and savings to access system designers. MCLASS enclosures are engineered to house FlexPower® power management boards alongside Mercury Security® access panels in one compact, secure system. The E8M can be configured for a maximum of twelve doors with dual voltage distribution.

To prevent damage to system electronics, the backplate separates from the enclosure for access hardware mounting in the shop while wiring is pulled to the enclosure at the job site. Once configured, the backplate can be re-mounted for final ties and checkout.

### Features


- Mounts LSP power and access hardware in a variety of combinations
- Removable backplate simplifies job installation
- Protected AC input terminal - meets arc protection requirements
- AC on/off circuit breaker switch
- Pre-engineered access mounting pattern
  - ◆ Power and distribution boards are mounted and pre-wired
  - ◆ Access boards mount on provided threaded standoffs
- Mechanical upgrades
  - ◆ Removable door with quick disconnect grounding strap
  - ◆ 6.5" enclosure depth accommodates 12Ah battery sizes
  - ◆ Lock with two (2) keys and installed tamper switch
  - ◆ 16 Gauge steel with LSP black textured finish
  - ◆ Multiple knockouts all four sides

Part No.	Door Count	Description	Weight
E8M	8 - 12 Doors	Enclosure with main backplate	70 lbs

E8 enclosure size: 36H x 30W x 6.5D



### Custom Backplate System



### Flexible Mounting Pattern

The E8M backplates are designed with a unique Mercury mounting pattern to provide the installer with a configuration mechanism capable of supporting up to 12 doors with system and lock power in an extremely efficient manner. The backplate is removable and mounts controllers and LSP modules in both single and dual voltage configurations.

The E8M1 variant adds a door backplate for expansion of distribution modules or up to four more controllers (see E8M1 datasheet).

The 6.50" cabinet depth allows up to 12Ah battery sizes for greater stand-by time.

### LSP/Mercury Joint UL/CUL Listing

Any combination of listed LSP and Mercury controllers may be configured and retain UL/CUL system listing.




**E8M Mercury Mounting Guide**


Mercury	Slots	Area
MR52 / LPxx	6	6 x 8
MR16in / MR16out	6	6 x 8
LP2500 / MUX8	6	6 x 5
LP1501 / MR51e	1	5.5 x 3.6 (bracket)
MR50	1	4.25 x 2.75

**Enclosure Features**


- ◆ **Custom Backplate**
  - Light weight aluminum with AC and battery slots to protect cables
  - LSP pre-wired power modules reduce installation time
  - Front side screw in standoffs simplifies panel installation
  - Wide wire management channels for panduit or tie wrap
- ◆ **Mechanical**
  - Protected AC cover with on/off circuit breaker for maintenance safety
  - Pre-drilled mounting holes for easy field upgrades
  - 6.5" cabinet depth accommodates large battery sets
  - Removable door with "fast disconnect" ground strap
  - Multiple knockouts all four sides




**Additional E8M Enclosure Patterns**




Main backplate  
6 boards



Main with door mount  
10 boards



Main backplate  
8 boards





**NOTE** - Although the E8M3 will physically hold up to 14 Mercury controllers, there may not be enough power or distribution space available for all configurations.

E8 Mechanical Specification

E8 Enclosure Dimensions (H x W x D)

36.00" x 30.00" x 6.50" (91 x 76 x 16.5 cm)



**[lifesafetypower.com](http://lifesafetypower.com)**

(888) 577-2898  
info1@lifesafetypower.com

Specifications subject to change without notice.

© 2022 LifeSafety Power LLC. All rights reserved. LifeSafety Power and FlexPower are registered trademarks of LifeSafety Power LLC. All other trademarks and copyrights are the property of their respective owners.

Mercury Security is a registered trademark of Mercury Security.

P01-648A 07/22

**LifeSafety Power**

10027 S. 51st Street, Suite 102  
Phoenix, AZ 85044 USA