



PNEUMATIC PUSH BUTTONS

ACCESS CONTROL PUSH BUTTON
WITH MECHANICAL PNEUMATIC HOLD TIME

LEARN MORE



click or scan



DESCRIPTION

BEA's **PNEUMATIC PUSH BUTTONS** are ruggedized, including stainless steel faceplates and colored, anodized aluminum buttons, appropriate for most indoor applications.

The device is uniquely designed to minimize the number of moving parts, in turn reducing the wear and tear of the button and extending the life of the device.

Upon activation, the user-defined time delay initiates without additional mechanical action or the need of external power.



Customizable

Adjustable time delay of 2 – 60 seconds

Standards Compliant

Listed UL 508 / CSA C22.2 No 14-10 with MET LABS, File #E113051

Various Styles

Buttons available in 1 5/8 inch (standard) or 2 inch (large) sizes


Meet Your Application Needs

Available in a variety of combinations of color, text and logo upon request

Tested To Last

Tested to perform greater than 1 million operations

APPLICATIONS

















Request-To-Exit

TECHNICAL SPECIFICATIONS

Technology	Pneumatic
Faceplate Dimensions	
Single	2 ¾" (W) x 4 ½" (H)
Jamb	1 ¾" (W) x 4 ½" (H)
Visual Style	Red Button with "Push to Exit" text Blue Button with Handicap Logo Green Button with "Push to Exit" text
Materials	Stainless steel faceplate with colored, anodized aluminum button
Switch Rating	5 A @ 125 VAC
Time Range	2 – 60 s ±15%, adjustable
Repeat Accuracy	±5% @ 72 °F
Operating Temperature	Rated for indoor use only -15 – 120 °F
Timer Life	1 million operations

PRODUCT SERIES

 <p>10ACPBDA1 2" Jamb, Red button, Text only</p>	 <p>10ACPBDA2 2" Single, Red button, Text only</p>	 <p>10ACPBDA3 1 ½" Jamb, Red button, Text only</p>
 <p>10ACPBDA4 1 ½" Single, Red button, Text only</p>	 <p>10ACPBDA5 2" Jamb, Blue button, Logo only</p>	 <p>10ACPBDA6 2" Single, Blue button, Logo only</p>
 <p>10ACPBDA7 1 ½" Jamb, Blue button, Logo only</p>	 <p>10ACPBDA8 1 ½" Single, Blue button, Logo only</p>	 <p>10ACPBDA9 2" Jamb, Green button, Text only</p>
 <p>10ACPBDA10 2" Single, Green button, Text only</p>	 <p>10ACPBDA11 1 ½" Jamb, Green button, Text only</p>	 <p>10ACPBDA12 1 ½" Single, Green button, Text only</p>
 <p>10BOX24SGSM Single surface mount</p>	 <p>10BOXJAMBST Jamb surface mount</p>	

DISCLAIMER Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

WWW.BEASENSORS.COM



BEA AMERICAS / RIDC Park West / 100 Enterprise Drive / Pittsburgh, PA
 T 1-800-523-2462 / F 1-888-523-2462 / E info-us@BEAsensors.com

A Halma company