



# RESTROOM KIT

FOR SINGLE OCCUPANCY NORMALLY LOCKED / UNLOCKED RESTROOMS



## LEARN MORE



click or scan

## CERTIFICATIONS



## DESCRIPTION

BEA's **RESTROOM KIT** is designed for both normally locked and normally unlocked single occupancy restrooms.

The kit's control center is the **BR3-X**, a programmable 3-relay advanced logic module featuring restroom control functionality. The **BR3-X** can also power an electric locking device by using the WET output on Relay 1.



### Advanced Logic With Restroom Functionality

BR3-X, 13 function advanced logic module, controls locking and sequencing functionality

### Highly Visible And Audible

Occupied Indicator with LED

### Visual Lock Confirmation

Push to Lock Button with LED

### Door Position Reset For Proper Functionality

Door position switch ensures proper positioning of door before resetting the system

### Code Compliant

Ontario Regulation 368/13 compliant

## APPLICATIONS



To Enter Restroom



To Exit Restroom

## TECHNICAL SPECIFICATIONS

### BR3-X

<b>Supply Voltage</b>	12 – 24 VAC / VDC ±10%
<b>Power Consumption</b>	30 – 130 mA; DRY Output
<b>Temperature Range*</b>	-15 – 150 °F
<b>Relay Hold Time</b>	Up to 60 seconds per relay
<b>Delay Between Relays</b>	Up to 60 seconds with ¼, ½ and ¾ second options
<b>Housing Material</b>	ABS Plastic
<b>Input Specifications</b>	
Inputs 1, 2, 3, 4	DRY contact
WET Input	5 – 24 VAC / VDC ±10%
<b>Contact Rating</b>	
Relay 1 (DRY)	3 A @ 24 VAC / 30 VDC
Relay 1 (WET)	1 A
Relay 2 (DRY)	3 A @ 24 VAC / 30 VDC
Relay 3 (DRY)	1 A @ 24 VAC / 30 VDC
<b>Dimensions</b>	5 ½" (W) × 2 ½" (H) × 1" (D)

### 10LEDSOUNDER

<b>Voltage</b>	12 – 24 VAC / VDC ±10%
<b>Indication</b>	Audible buzzer (selectable on / off) and visual LED
<b>Text Inserts</b>	10
<b>Material</b>	Stainless steel & PC
<b>Certifications</b>	FCC

### 10PTLBUTTON

<b>Switch</b>	SPST
<b>Voltage Max.</b>	125 / 250 VAC
<b>Current Max.</b>	10 A
<b>Power Max.</b>	373 W
<b>Electrical Configuration</b>	SPDT
<b>High Volt Bulb</b>	
Input Voltage	15 – 24 VAC / VDC
Current	0.06 A
<b>Low Volt Bulb</b>	
Input Voltage	12 – 14 VAC / VDC
Current	0.19 A
<b>Dimensions</b>	2 13/25" (W) × 4 13/25" (H) × 3/4" (D)


### 10SWITCH1084

<b>Switching Voltage Max.</b>	30 VAC / VDC
<b>Switching Current Max.</b>	0.25 A
<b>Power Max.</b>	3.0 W
<b>Electrical Configuration</b>	SPDT
<b>Loop Type</b>	Open or Close
<b>Gap Distance Max.</b>	2"

\*If powered by AC voltage and using WET output to convert to DC voltage and current draw of device is greater than 0.9 A, the upper temperature range is 130 °F

**DISCLAIMER** Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

## PRODUCT SERIES



**10RESTROOMKIT**  
Restroom kit




**10BR3X**  
3-Relay logic module



**10EMERGENCYKIT**  
Emergency add-on kit



**10LEDSOUNDER**  
Occupied indicator



**10PTLBUTTON**  
"Push To Lock" button



**10SWITCH1084**  
Door position switch



**10STRIKERE**  
Rim exit electric strike



**10STRIKECU**  
Universal cylindrical electric strike



**10PS12-24**  
UL / ULC Listed power supply



**1012VAC**  
12 VAC (20 VA)  
transformer



**1024VAC**  
24 VAC (40 VA)  
transformer