

SINGLE GANG PUSH PLATES

STAINLESS STEEL ACTUATORS







LEARN MORE




click or scan

DESCRIPTION

BEA's **SINGLE GANG PUSH PLATES** improve overall door access, enhance accessibility for those with limited mobility or disabilities and seamlessly integrate with an automatic door's activation.

These ADA-compliant push plates are available in a variety of popular faceplate graphic options. This product may be hard wired to the door operator or connected to BEA's line of wireless transmitters.





Robust Design

½16 inch thick stainless steel for maximum durability

Vandal Resistant

Concealed fasteners to minimize vandalism

Available In Complete Kits

Complete kits available including plates, mounting boxes and optional wireless devices for ease of ordering

Enhances Accessibility

ADA-compliant push plates are available in a variety of popular faceplate graphic options

Highly Compatible And Customizable

Compatible with both surface and flush mount boxes; various text, graphic and logo options available

APPLICATIONS







Request-To-Exit

Low Energy Doors

TECHNICAL SPECIFICATIONS

Faceplate Material	16 gauge, 304 2B Stainless Steel	
Backplate Material	1/8" thick, Aluminum	
Mounting Screws	Stainless Steel, 6-32 × 1" & 8-32 × 1" Allen Head Size: 5/4	
Cherry Switch	Single-pole, 15 A, COM / NO / NC, UL Recognized	
Compatible Wireless Frequencies	900, 433 or 300 MHz	

PRODUCT SERIES



10PBO241 "Push to Open" text & handicap logo



Handicap logo only





10BOX24SGSM

Standard single gang surface mount box $(2 \frac{3}{4}'' \times 4 \frac{1}{2}'')$

DISCLAIMER Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

