




MARINE/RV SERIES



SPECIFICATIONS

Model	Application	Nominal Voltage	CCA	Rated Capacity AH	Reserve Capacity	Series/Parallel	Approx. Dimensions: Inches			Minimum Weight lbs.	Terminal Type
							Length	Width	Height		
DCM-12800-G24	AGM Dual Purpose	12.0	550	79	150	6/6	10.24	6.61	9.17	50.72	SAE
PSL-BT-12750-G24	Lithium Deep Cycle	12.8	N/A	75	180	4/4	10.20	6.60	8.60	20.5	M8
PSL-BT-24400-G24	Lithium Deep Cycle	25.6	N/A	40	96	1/4	10.20	6.60	8.60	20.5	M8
DCM-12900-G27	AGM Dual Purpose	12.0	800	92	200	6/6	12.05	6.61	9.11	62.84	SAE
PSL-BT-121000-G27	Lithium Deep Cycle	12.8	N/A	100	240	4/4	12.08	6.61	8.70	28.2	M8
PSL-BT-24500-G27	Lithium Deep Cycle	25.6	N/A	50	120	1/4	12.08	6.61	8.70	28.2	M8
DCM-121050-G31	AGM Dual Purpose	12.0	825	105	200	6/6	12.99	6.81	9.27	67.47	SAE
PSL-BT-121250-G31	Lithium Deep Cycle	12.8	N/A	125	300	4/4	12.95	6.77	8.80	33.3	M8
PSL-BT-24600-G31	Lithium Deep Cycle	25.6	N/A	60	144	1/4	12.95	6.77	8.80	33.3	M8
PSL-BT-36400-G31	Lithium Deep Cycle	38.4	N/A	40	96	1/4	12.95	6.77	8.80	33.3	M8




DROP-IN REPLACEMENT



MAINTENANCE FREE



FLEXIBLE INSTALLATION



PARALLEL/SERIES INSTALLATIONS

SCAN ME

