

# OEI-371S-H-W Indoor Station

## Overview

OEI-371S-H-W indoor station is one of the terminals in the digital building intercom system, with functions of video intercom, security alarm, network camera monitoring, etc., providing a safe and comfortable living environment for residents. It can be widely used in building systems such as smart communities, villas, and office parks



## Features

- Rugged ABS casing and glass panel.
- 1024\*600 HD touch screen.
- Batch configuration transfer.
- Remote opening of linked door stations, one-key opening.
- Network camera monitoring, security alarm.

## Ordering Information

| Model        | Remarks        |
|--------------|----------------|
| OEI-371S-H-W | Indoor Station |

### Zhejiang Uniview Technologies Co., Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2022 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\* Product specifications and availability are subject to change without notice.

## Specifications

| Parameter                  | Description   |
|----------------------------|---|
| Power                      | DC12V±25%   |
| Screen resolution          | 1024×600  |
| Screen                     | 7-inch ultra-thin TFT LCD screen  |
| Operation system           | Linux   |
| Audio quality              | Noise suppression,echo cancellation and AGC                                   |
| Audio input                | 1 built-in omnidirectional microphone   |
| Audio output               | 1 built-in speaker  |
| Audio compression standard | MP3 G711  |
| Audio compression rate     | 128Kbps   |
| Protocol                   | UNV private protocol  |
| Power consumption          | <10W  |
| Weight                     | 377g  |
| Interface                  | Power*1, network*1, Wi-Fi*1, RS485*1, IO output*2, IO input*8, TF card slot*1 |
| Network                    | 100Mbps network port, supports IEEE802.3af PoE power supply                   |
| Dimensions (L×H×W)         | 193.2mm×143.4mm×24.3mm  |
| Operating environment      | -10°C to +55°C, 10% to 90%, non-condensing, indoor                            |

## Dimensions

